BAKERY

MJPE318

MULTIDECK DEEP MEDIUM TEMPERATURE CABINET



ENHANCED ENERGY EFFICIENCY & VERSATILITY



PRODUCT BENEFITS

- Ergonomic design for easy access
- Alternate shelving layouts to optimise merchandising _
- Optimised display with LED lighting -
- Dual air curtain technology
- Low Total Energy Consumption (TEC)
- Longer merchandise shelf life -
- Product temperature compliance
- Simple to install and maintain
- Designed for modular configurations

STANDARD FEATURES

- Internal and external powder coating
- Single row of 4000K LED canopy lighting -
- _ 4 rows of 550mm powder coated shelves
- Undershelf lighting 4000K -
- Wire product fences 75mm
- Adjustable base wire tray with 115mm front
- Mirror Kit
- Ticket strips
- Wire air return grill
- Galvanised base
- Night blind manual slow release
- Rubber bumper
- Evaporator assembly fitted with valve
- EC fan motors
- Digital thermometer display fitted
- Alarm probe fitted with conduit and draw wire

CUSTOMISATIONS Shelving & Base Shelf

- Stainless steel reinforced solid shelving and base tray
- Additional shelves and brackets
- Roller shelving (optional product divider)
- Hang sell and bar
- Wire or acrylic shelf fences (45mm, 75mm)
- Adjustable wire base rack with product stop (75mm or 115mm)

Lighting

- Canopy / Under-shelf lighting
- Premium lighting available

Ends

- Solid mirror ends / Glass view ends
- Common end
- Acrylic full height system divider

Bumper


- Stainless steel bumper (single or double rail)

Other

- Rear mirror kit
- Top mount piping
- Rear dress panels -
- Valance panels top or lower rear -
- Technology Solutions
- Electronic shelf labels or video rail -

Energy & Sustainability

- Air-Guide technology
- Motorised night blind _
- Door solutions



805

1015


1095

15

130

145

310



Crown Ends:

1250, 1875, 2500, 3750 1562, 1875 (MJPE218)

CLASS

AVAILABLE DEPTHS

MJPE118 - Narrow: 895 MJPE218 - Standard: 995 MJPE318 - Deep: 1095

AVAILABLE COLOURS



Additional Information

All Dimensions shown in Millimetres (mm) unless otherwise stated. Dimensions and features are subject to change. Please obtain current technical information prior to order confirmation.

NOTE: We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such change not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or Shipped.

© 2020 Hussmann Corporation - Version - V.1.0

Australia Head Office

66 Glendenning Road Glendenning, NSW 2761 Australia

ph. +612 8805 0400

www.hussmann.com.au

HUSSMANN®

3M1







315

Excluding Ends: