



Note:1. For the output power, the electromotor normal stipulated output power.

2. Please use this numerical value, if you want to express the electrical expenditure.

Description		Commercial refrigerator		
Model Number		SUR-1571HP (AUH) -NN		
Dimensions	Overall Dimension (W X D X H)	1500mm	750+(40) mm	850mm
	Outside Dimension (W X D X H)	1094mm	587mm	573mm
Effective Volume		138L		
Material	Overall Material	Stainless Steel Plate OUT:TTS443M-NO.4		
	Door	Stainless Steel Plate OUT:TTS443M-NO.4		
	Inner Material	Stainless Steel Plate IN:JYH21CT-2B		
	Net Rack	P.E. and painted steel wire footings		
Performance	Insulation	Cyclopentane Horniness Froth		
	Condition	External Temperature 30°C With no load not exposed to direct sunlight		
	Internal Temperature	Below 0°C		
	Temperature Setting Range	-4~10°C		
Freezing Assembly	Compressor	Obturation Completed		
	Condenser	Fin Type Forced Circulation Of Cold Air		
	Evaporator	Fin Type Forced Circulation		
	Refrigerant	R290		
	Fan Motors	Evaporator	Single Phase INPUT DC 12V 6W	
		Condenser	Single Phase INPUT DC 12V 8.4W	
	Tem. Meter	Mini Computer Controlled		
Defrost	Mini Computer controlled, Auto heat defrost			
Power Specification	Power	Single-Phase 220-240V 50HZ		
	Efficiency Consumption	Defrosting 254W		
		Cooling 260W		
Power	Power Cord	Lenth: 3.0m		
	Applicable Socket	2-plug with gronging end 10A 250V		
Table Foot	Colophony Control Bound 130mm			
Accessories	—			
Others	Condenser Filternet, figure thermometer			
Weight	105kg			

Panasonic Appliances Cold Chain (Dalian) Co., Ltd	APPROVALS	DESIGN	SCALE	SUR-1571HP (AUH) -NN		PART CODE	SUR-1571HP(AUH)-NN
	Li Fei 22.02.23	Zhang Jinqiu 22.02.23	A4 1/30	DATE	22.02.23	PRODUCT NAME	

The specifications are subject to partial changes due to improvements CAD 00