

# Galaxy H150 TN SLD



H 150

P 88

L 94 • 125 • 188

meat • sandwiches • drinks • dairy • fresh products

Semi-vertical multideck chiller with sliding glass doors, fitted with an environmentally friendly plug-in R290 refrigeration system for the display of meat, dairy products, fresh and pre-packed products

#### Installation

Plug-in

#### Cabinet Front Height

427 mm

#### Configuration

Semi Vertical - Sliding Glass Doors

#### Refrigerant

R290

#### Refrigeration System

Ventilated (RV)

#### Compressor

Hermetic

#### Defrost

Off cycle

#### Temperature Range

- 1 / + 1 °C

#### Climate Class

3M1

#### Operating Conditions

25°C Ambient / 60% RH

#### Power Supply

230V / 1 Ph / 50Hz

#### Electrical Amperage 94

10A

#### Electrical Amperage 125

10A

#### Electrical Amperage 188

20A

#### Closing System

Glass Sliding Doors - Double Glass

#### Side Panels

- Panoramic End Panel - safety glass (Std)
- Solid Mirror End Panel (Optional)

#### Shelves No.

3 with LED (Lighting Standard)

#### Shelves Type

Solid

#### Shelves Fence

Perspex

#### Lighting

- 4000K LED Canopy (Std)
- 4000K Undershef LED Shelf (Std)
- 3000K LED Colour (Optional)

#### Inside Colour

RAL 9005 - Jet Black (Std)

#### Outside Colour

RAL 9005 - Jet Black (Std)

#### Side Panels Colour

RAL 9005 - Jet Black (Std)

#### Base/ Equipment Handling

- Castors with brake (Std)
- 4 adjustable feet (optional)



Sliding Glass Door Low Height Merchandiser

#### Inside Colour



#### Outside Colour



#### Side Panels Colour



RAL colour system or stainless steel options available ex. factory \*POA



## Galaxy H150 TN SLD

		94	125	188
External Dimensions PANORAMIC (LxDxH)	Swivel Castors	993 x 908 x 1575 mm	1300 x 908 x 1575 mm	1935 x 908 x 1575 mm
	Adjustable Feet	993 x 908 x 1510 mm	1300 x 908 x 1510 mm	1935 x 908 x 1510 mm
External Dimensions SOLID (LxDxH)	Swivel Castors	1011 x 908 x 1575 mm	1318 x 908 x 1575 mm	1953 x 908 x 1575 mm
	Adjustable Feet	1011 x 908 x 1510 mm	1318 x 908 x 1510 mm	1953 x 908 x 1510 mm
Capacity (gross/net)		491/386 lt	651/ 512 lt	983 / 773 lt
Net Weight		200 kg	240 kg	340 kg
Refrigeration		Ventilated		
Refrigerant		R290 / GWP3		
Climate Class		3M1		
Operating Conditions		25 °C / 60 % RH		
Temperature Range		- 1 / + 1 °C		
Compressor		1 Hermetic		2 Hermetic
Defrost		Off Cycle		
Power Supply		230 V / 1 ph		
Power Amp at Plug <i>20A Plug supplied - 56 Series</i>		10	10	20
Lighting - Canopy		LED 4000K		
Number of Shelves		3	3	3
Dimensions - Shelf Line 1		350 x 94 mm	350 x 125 mm	350 x 188 mm (2 Shelves)
Dimensions - Shelf Line 2 + 3		400 x 94 mm	400 x 125 mm	400 x 188 mm (2 Shelves)
Dimensions Base		503 x 94 mm	503 x 125 mm	503 x 188 mm (2 Shelves)
Shelf Bracket Adjustment - 25.4 Pitch		0°, 10°, 20°		
Shelf Lighting - Undershef		LED 4000K		
Shelf Merchandising		H30 Plexiglass Product Stop   H39 Price Holder Ticket Strip		
Closing System		Double Glazed Glass Doors - Sliding		
Swivel Castors with Brakes Standard <i>Leveling Feet Optional</i>		STD	STD	STD
Exterior Colour		RAL 9005 JET BLACK - Standard		
Interior Colour		RAL 9005 JET BLACK - Standard		
End Panel		Panoramic (25mm)	Solid (34mm)	Solid with Mirror (34mm)
Standard Configuration		REFRIGERANT - R290   LIGHTING - Canopy & Under Shelf 4000K END PANELS - Panoramic   CLOSING SYSTEM - Open Front   BASE - Swivel Castors		

