

# IGNIS

R290 HEAT PUMP SYSTEMS



NATURAL HVAC SYSTEMS SOLUTIONS  
FOR A MORE SUSTAINABLE FUTURE



## PRODUCT DESCRIPTION

Medium power range reversible heat pumps with the heating power from 30 kW to 145 kW are designed for commercial and industrial buildings with medium power demand. Manufactured using R290 refrigerant only and full-inverter technology the units are a part of the extremely economical and environmentally friendly Refra product line. These pumps can be used for heating purposes at ambient temperature of -15° or higher as well as for cooling purposes with the capacity of 30 kW to 125 kW. This dual solution is very efficient in terms of price, installation and space, as there is no need to install two separate systems.

Compact frame construction is assembled with high-quality EC fan motor technology, finned tube heat exchangers and reciprocating compressors. Galvanized steel and powder coated frame with a reliable 20 mm non-flammable acoustical PU foam insulation material ensures proper unit protection as well as noise reduction. An additional 50 mm rock wool material can be supplemented for a super silent unit operation.

## PARTS INCLUDED

- Bitzer reciprocating compressors (Ex II-3G) with oil charge and oil level monitoring/differential pressure switch;
- Polymer powder painted RAL7035 frame;
- Frequency inverters on all compressors;
- HP/LP pressure switch per circuit;
- HP/LP pressure gauges per circuit;
- Necessary pressure and temperature probes;
- Liquid receiver per circuit;
- Air cooled condenser (copper tubes - aluminium fins);
- 4-way valve for reversible operation;
- Double safety valves per circuit;
- Filter drier on liquid line per circuit;
- Sight glass on liquid line per circuit;
- Magnetic expansion valve per circuit;
- Control board with Siemens Climatix controller;
- Suction line accumulator per circuit;
- Vibration absorbers;
- BPHE evaporator;
- R290 leak detector;
- Emergency EX fan;
- EC Fans;
- Muffler.

## TECHNICAL PARAMETERS

Calculations are made for basic units without additional options

Model		IGN 107	IGN 108	IGN 109	IGN 110	IGN 111
<b>Standard version</b>						
Heating capacity <sup>1</sup>	kW	68,1	75,1	86,7	98,5	111,2
Power consumption	kW	19,3	21,8	24,9	28,1	31,9
COP		3,5	3,5	3,5	3,5	3,5
SCOP		4,2	4,4	4,4	4,5	4,5
SSHEE	%	165	173	173	177	177
Refrigeration capacity <sup>2</sup>	kW	62,2	67,9	78,2	87,5	97,5
Power consumption	kW	19,4	22,2	26,2	29,7	33,7
EER		3,2	3,1	3,0	2,9	2,9

## System data

Refrigerant	Type	R290				
Number of compressors	n	1	1	1	1	1
Refrigerant quantity per circuit <sup>3</sup>	kg	10,9	10,9	10,9	10,9	12,2
Inlet/Outlet connection	DN	50	50	65	65	65
Sound pressure level in 10m <sup>4</sup>	dB	52	52	52	52	52

## Fan

Type		EC				
Number of fans	n	2	2	2	2	2
Air flow	m³/h	47284	47284	47284	47284	47284

## Plate heat exchanger

Number of plate heat exchangers	n	1	1	1	1	1
Flow rate heating <sup>1</sup>	m³/h	12,7	14,0	16,1	18,4	20,7
Pressure drop heating	kPa	13,1	15,6	20,3	25,8	17,4
Flow rate cooling <sup>2</sup>	m³/h	11,9	12,9	14,9	16,7	18,6
Pressure drop heating	kPa	14,3	16,6	21,3	25,9	17,5

## Power supply

Voltage		3-400V / 50Hz				
Max. power consumption	A	36,5	41,0	47,9	55,2	65,2

## Dimensions and weight

Length	mm	3105	3105	3105	3105	3105
Width	mm	1363	1363	1363	1363	1363
Height	mm	2340	2340	2340	2340	2340
Operating weight	kg	1100	1120	1150	1170	1200

<sup>1</sup> Outside air temperature 7°C, medium temperature 40/45°C, medium EG 35%.

<sup>2</sup> Outside air temperature 35°C, medium temperature 12/7°C, medium EG 35%.

<sup>3</sup> Theoretical values refer to the basic unit. The actual amount of gas charge in the unit may differ.

<sup>4</sup> Sound pressure level at a distance of 10m in the free field and at the extended point, tolerance +/-2dB(A).



## Additional Information

All Dimensions shown in Millimetres (mm) unless otherwise stated. Dimensions and features are subject to change. Please obtain current technical information prior to order confirmation.

**NOTE:** We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or Shipped.

## Australia Head Office

66 Glendenning Road Glendenning, NSW 2761 Australia

ph. +612 8805 0400

w. hussmann.com.au

# HUSSmann®